



TLBE *Head Shredder for mini-excavator*

The TLBE shredding head is perfect for triturating grass, canes and shrubs generally up to 3 cm, located near ditches, banks and all sorts of very steep lands. It can be applied to excavators weighing from 1.5 to 4 tons.



TLBE

Head Shredder for mini-excavator



Mod.			Kg	(g/min.)	L/1'	Press. BAR	kit	rotore mm		
TLBE - 50	650	540	180	2000	20/30	250	6	-	108	2
TLBE - 70	850	740	200	2000	30/45	250	-	7	108	2
TLBE - 90	1050	940	220	2000	30/45	250	-	9	108	2
TLBE - 100	1150	1040	230	2000	40/60	250	-	10	108	2
TLBE - 110	1250	1140	250	2000	40/60	250	-	11	108	2
TLBE - 120	1350	1240	270	2000	40/60	250	-	12	108	2

The technical data, specifications, characteristics and pictures are not binding for the manufacturer.

STANDARD EQUIPMENT

- Linkage device
- **Hydraulic motor group 2**
- Valve anti-cavitation
- Belt drive
- Rotor with smooth hammers
- Interior counterblades
- Front safety with chains
- Rear safety in rubber
- Lateral skids
- Rear adjustable roller with scraper
- Special paint powder or liquid (Primer and enamel)
- Rubber protection

ACCESSORIES ON REQUEST

- 1 Oscillating saddle
- 2 Pressure relief valve with flow regulator
- 3 Hydraulic motor group 3 instead of group 2
- 4 Safety pin saddle*

*Personalized saddle will be subjected to additional charge



LIPA s.r.l.
65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170
info@lipa-srl.it www.lipa-srl.it

CE
MADE IN ITALY